

View Online at <https://aerobasegroup.com/nsn/5340-01-467-4717>

First Leg Length:

4.750 inches

Second Leg Length:

7.750 inches

End Application:

Striker

Second Leg Width:

3.000 inches

Second Leg Corner Radius:

0.250 inches

First Leg Hole Diameter:

0.343 inches

Second Leg Distance Between Hole Centers Along Length:

3.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

3.380 inches

Second Leg Slot Length:

0.750 inches

Second Leg Slot Width:

0.343 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

3.000 inches

First Leg End Width:

0.320 inches

First Leg Distance Between Hole Centers Along Width:

1.457 inches

First Leg Distance Between Hole Centers Along Length:

1.780 inches

First Leg Distance From Edge To Hole Center Along Width:

0.781 inches

First Leg Distance From Edge To Hole Center Along Length:

0.620 inches

First Leg Style:

Angle

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.750 radians

Product Name:

Support, bracket, vms

Material:

Aluminum alloy 6061

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0