

View Online at <https://aerobasegroup.com/nsn/5340-01-467-9505>

Mounting Hole Type:

Plain

First Leg Length:

2.000 inches

Second Leg Length:

3.620 inches

End Application:

Used on bradley fighting vehicle systems

Second Leg Width:

3.500 inches

Second Leg End Width:

3.500 inches

First Leg Slot Length:

0.620 inches

First Leg Slot Width:

Between 0.406 inches and 0.460 inches

Second Leg Distance Between Hole Centers Along Width:

1.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.880 inches

Second Leg Distance From Edge To Hole Center Along Length:

2.620 inches

Second Leg Slot Length:

1.000 inches

Second Leg Slot Width:

Between 0.406 inches and 0.460 inches

First Leg Thickness:

0.187 inches

Second Leg Thickness:

0.187 inches

First Leg Width:

3.500 inches

First Leg End Width:

3.500 inches

First Leg Distance Between Hole Centers Along Width:

1.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Side Radius:

0.380 inches

First Leg Style:

Side radius

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.38 radians

Second Leg Chamfer Angle:

45.0 degrees

Material:

Steel

Material Specification:

Astm a36/a, 36m-97a assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0