

View Online at <https://aerobasegroup.com/nsn/5340-01-467-9936>

First Leg Length:

2.050 inches

Second Leg Length:

7.100 inches

End Application:

Command post carrier 2350013689528 bradley infantry fighting vehcile (m2, m2a1, m2a2); cavalry fighting vehicle (m3, m3a1, m3a2)

Second Leg Width:

10.500 inches

First Leg Slot Length:

0.500 inches

First Leg Slot Width:

0.380 inches

Second Leg Distance Between Hole Centers Along Width:

4.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.030 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

Second Leg Slot Length:

0.500 inches

Second Leg Slot Width:

0.310 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

9.600 inches

First Leg Distance Between Hole Centers Along Length:

4.500 inches

First Leg Distance From Edge To Hole Center Along Width:

1.310 inches

First Leg Distance From Edge To Hole Center Along Length:

1.200 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-250/6 federal specification 1st material response or qq-a-250/7 federal specification 1st material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0