

View Online at <https://aerobasegroup.com/nsn/5340-01-469-0794>

First Leg Length:

Between 4.320 inches and 4.440 inches

Second Leg Length:

Between 4.320 inches and 4.440 inches

End Application:

Nsn5420-01-430-5403, carrier bridge launching abrams m-1

Second Leg Width:

Between 4.320 inches and 4.440 inches

Second Leg End Width:

Between 3.820 inches and 3.940 inches

First Leg Slot Length:

Between 0.970 inches and 1.030 inches

First Leg Slot Width:

Between 0.404 inches and 0.414 inches

Second Leg Distance From Edge To Hole Center Along Width:

2.195 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.125 inches

Second Leg Slot Length:

Between 3.590 inches and 3.650 inches

Second Leg Slot Width:

Between 0.404 inches and 0.414 inches

First Leg Thickness:

Between 0.190 inches and 0.310 inches

Second Leg Thickness:

Between 0.190 inches and 0.310 inches

First Leg Width:

Between 4.320 inches and 4.440 inches

First Leg End Width:

Between 3.820 inches and 3.940 inches

First Leg Distance Between Hole Centers Along Width:

1.250 inches

First Leg Distance From Edge To Hole Center Along Width:

1.570 inches

First Leg Distance From Edge To Hole Center Along Length:

1.440 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.190 radians and 0.310 radians

First Leg Chamfer Angle:

Between 43.0 degrees and 47.0 degrees

Second Leg Chamfer Angle:

Between 43.0 degrees and 47.0 degrees

Special Features:

Material is .25 inches thk

Material:

Steel

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0