NSN 5340-01-469-0794

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-469-0794

First Leg Length:

Between 4.320 inches and 4.440 inches

Second Leg Length:

Between 4.320 inches and 4.440 inches

End Application:

Nsn5420-01-430-5403, carrier bridge launching abrams m-1

Second Leg Width:

Between 4.320 inches and 4.440 inches

Second Leg End Width:

Between 3.820 inches and 3.940 inches

First Leg Slot Length:

Between 0.970 inches and 1.030 inches

First Leg Slot Width:

Between 0.404 inches and 0.414 inches

Second Leg Distance From Edge To Hole Center Along Width:

2.195 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.125 inches

Second Leg Slot Length:

Between 3.590 inches and 3.650 inches

Second Leg Slot Width:

Between 0.404 inches and 0.414 inches

First Leg Thickness:

Between 0.190 inches and 0.310 inches

Second Leg Thickness:

Between 0.190 inches and 0.310 inches

First Leg Width:

Between 4.320 inches and 4.440 inches

First Leg End Width:

Between 3.820 inches and 3.940 inches

First Leg Distance Between Hole Centers Along Width:

1.250 inches

First Leg Distance From Edge To Hole Center Along Width:

1.570 inches

First Leg Distance From Edge To Hole Center Along Length:

1.440 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Chamfered ends

NSN 5340-01-469-0794 Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:
One slot
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
Between 0.190 radians and 0.310 radians
First Leg Chamfer Angle:
Between 43.0 degrees and 47.0 degrees
Second Leg Chamfer Angle:
Between 43.0 degrees and 47.0 degrees
Special Features:
Material is .25 inches thk
Material:
Steel
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A042a0