NSN 5340-01-472-6282

Corner Brace - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-472-6282

| Material Thickness: |
|--|
| 0.060 inches |
| Mounting Hole Diameter: |
| 0.280 inches |
| First Leg Length: |
| 1.880 inches |
| Second Leg Length: |
| 14.380 inches |
| End Application: |
| Carrier, bridge launching; tank, abrams m-1 |
| Second Leg Width: |
| 0.500 inches |
| First Leg Hole Diameter: |
| 0.280 inches |
| Second Leg Hole Diameter: |
| 0.280 inches |
| Second Leg Distance From Edge To Hole Center Along Width: |
| 0.250 inches |
| Second Leg Distance From Edge To Hole Center Along Length: |
| 0.380 inches |
| First Leg Width: |
| 0.500 inches |
| First Leg Distance Between Hole Centers Along Length: |
| 9.750 inches |
| First Leg Distance From Edge To Hole Center Along Width: |
| 0.250 inches |
| First Leg Distance From Edge To Hole Center Along Length: |
| 1.380 inches |
| First Leg Distance Between First And Second Hole Centers Along Length: |
| 3.250 inches |
| First Leg Distance Between Second And Third Hole Centers Along Length: |
| 3.250 inches |
| First Leg Style: |
| Square |
| First Leg Hole Arrangement Style: |
| Four holes |
| Second Leg Hole Arrangement Style: |
| One hole |
| Hole Quantity: |
| 6 |
| Angle: |
| 90.0 degrees |

NSN 5340-01-472-6282Corner Brace - Page 2 of 2



| Second Leg Relationship To First Leg: |
|--|
| Identical |
| Material: |
| Aluminum alloy 6061 |
| Material Specification: |
| Qq-a-250/11 federal specification all material responses or astm b209 assn standard all material responses |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-std-171, 7.2.1 military standard all treatment responses |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A042a0 |
| Mil-std (military Standard): |
| Mil-std-171 spec. |
| |