

View Online at <https://aerobasegroup.com/nsn/5340-01-472-7210>

First Leg Length:

2.000 inches

Second Leg Length:

2.000 inches

End Application:

Carrier, bridge launching; tank, abrams m-1

Second Leg Width:

6.000 inches

First Leg Hole Diameter:

0.406 inches

Second Leg Hole Diameter:

0.875 inches

Second Leg Distance Between Hole Centers Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.820 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

6.000 inches

First Leg Distance Between Hole Centers Along Width:

4.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

0.625 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Material:

Steel

Material Specification:

Astm a36 assn standard all material responses or asme sa-36 assn standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-std-171, 5.1.1 military standard all treatment responses or mil-std-171, 5.2 military standard all treatment responses

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.