

View Online at <https://aerobasegroup.com/nsn/5340-01-472-7776>

First Leg Length:

2.930 inches

Second Leg Length:

6.000 inches

End Application:

Armored reconnaissance-airborne assault vehicle; fighting vehicle systems, bradle (bfvs)

Second Leg Width:

8.000 inches

Second Leg End Width:

1.500 inches

First Leg Hole Diameter:

0.500 inches

Second Leg Hole Diameter:

Between 0.350 inches and 0.400 inches

Second Leg Distance Between Upper Hole Centers Along Width:

5.500 inches

Second Leg Distance Between Hole Centers Along Length:

1.750 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

2.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.563 inches

First Leg Thickness:

0.188 inches

Second Leg Thickness:

0.188 inches

First Leg Width:

8.000 inches

First Leg Distance Between Hole Centers Along Width:

5.570 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

1.310 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

75.0 degrees

Product Name:

Bracket, angle, full function crew station

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Stm b209 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0