

View Online at <https://aerobasegroup.com/nsn/5340-01-472-7776>

**First Leg Length:**

2.930 inches

**Second Leg Length:**

6.000 inches

**End Application:**

Armored reconnaissance-airborne assault vehicle; fighting vehicle systems, bradle (bfvs)

**Second Leg Width:**

8.000 inches

**Second Leg End Width:**

1.500 inches

**First Leg Hole Diameter:**

0.500 inches

**Second Leg Hole Diameter:**

Between 0.350 inches and 0.400 inches

**Second Leg Distance Between Upper Hole Centers Along Width:**

5.500 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.750 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

2.750 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.563 inches

**First Leg Thickness:**

0.188 inches

**Second Leg Thickness:**

0.188 inches

**First Leg Width:**

8.000 inches

**First Leg Distance Between Hole Centers Along Width:**

5.570 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.310 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Angle

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

75.0 degrees

**Product Name:**

Bracket, angle, full function crew station

**Material:**

Aluminum alloy 5083 or aluminum alloy 5086

**Material Specification:**

Stm b209 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0