

View Online at <https://aerobasegroup.com/nsn/5340-01-473-9050>

First Leg Length:

2.380 inches

Second Leg Length:

2.250 inches

End Application:

Nimitz class cvn

First Leg Slot Length:

0.920 inches

First Leg Slot Width:

0.166 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

3.875 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

2.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.525 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.707 inches

Second Leg Slot Length:

0.439 inches

Second Leg Slot Width:

0.339 inches

First Leg Thickness:

0.188 inches

Second Leg Thickness:

0.188 inches

First Leg Width:

7.500 inches

First Leg End Width:

6.500 inches

First Leg Distance Between Hole Centers Along Width:

6.650 inches

First Leg Distance From Edge To Hole Center Along Width:

0.425 inches

First Leg Distance From Edge To Hole Center Along Length:

0.598 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

2 slots

Second Leg Hole Arrangement Style:

3 slots

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

90.0 degrees

Product Name:

Slide screw tuner bracket

Material:

Steel

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, finish -264 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-f-14072 spec.