

View Online at <https://aerobasegroup.com/nsn/5340-01-473-9050>

**First Leg Length:**

2.380 inches

**Second Leg Length:**

2.250 inches

**End Application:**

Nimitz class cvn

**First Leg Slot Length:**

0.920 inches

**First Leg Slot Width:**

0.166 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

3.875 inches

**Second Leg Distance Between Second And Third Hole Centers Along Width:**

2.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.525 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.707 inches

**Second Leg Slot Length:**

0.439 inches

**Second Leg Slot Width:**

0.339 inches

**First Leg Thickness:**

0.188 inches

**Second Leg Thickness:**

0.188 inches

**First Leg Width:**

7.500 inches

**First Leg End Width:**

6.500 inches

**First Leg Distance Between Hole Centers Along Width:**

6.650 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.425 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.598 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Hole Arrangement Style:**

3 slots

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

90.0 degrees

**First Leg Chamfer Angle:**

90.0 degrees

**Product Name:**

Slide screw tuner bracket

**Material:**

Steel

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072, finish -264 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-f-14072 spec.