

View Online at <https://aerobasegroup.com/nsn/5340-01-475-4604>

**First Leg Length:**

2.630 inches

**Second Leg Length:**

3.500 inches

**End Application:**

2350-01-432-1526; armored reconnaissance-airborne assault vehicle; fighting vehicle system, bradley (bfvs)

**Second Leg Width:**

2.750 inches

**Second Leg Corner Radius:**

0.120 inches

**First Leg Hole Diameter:**

Between 0.860 inches and 0.940 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 1.730 inches and 1.770 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.690 inches

**Second Leg Slot Length:**

0.500 inches

**Second Leg Slot Width:**

0.340 inches

**First Leg Thickness:**

0.190 inches

**Second Leg Thickness:**

0.190 inches

**First Leg Width:**

2.750 inches

**First Leg End Width:**

1.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.970 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.830 inches

**First Leg Style:**

Angle

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Product Name:**

Bracket, mounting, vehicle motion sensor

**Material:**

Aluminum alloy 5052 or aluminum alloy 5086

**Material Specification:**

Qq-a-250/7 federal specification single material response or qq-a-250/8 federal specification single material response or astm b209 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0