

View Online at <https://aerobasegroup.com/nsn/5340-01-484-7552>

Mounting Hole Type:

Plain

First Leg Length:

1.750 inches

Second Leg Length:

0.880 inches

Second Leg Width:

0.880 inches

First Leg Slot Length:

0.300 inches

First Leg Slot Width:

0.180 inches

Second Leg Distance Between Hole Centers Along Width:

0.400 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.400 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.440 inches

Second Leg Slot Length:

0.600 inches

Second Leg Slot Width:

0.180 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

0.880 inches

First Leg Distance Between Hole Centers Along Length:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.190 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.09 radians and 0.12 radians

Product Name:

Bracket, angle-attenuator

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, class 1a or class 3 military standard single treatment response

Style Designator:

Angle

Fsc Application Data:

Nha pn 11456678

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.