

View Online at <https://aerobasegroup.com/nsn/5340-01-484-7552>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.750 inches

**Second Leg Length:**

0.880 inches

**Second Leg Width:**

0.880 inches

**First Leg Slot Length:**

0.300 inches

**First Leg Slot Width:**

0.180 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.400 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.400 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.440 inches

**Second Leg Slot Length:**

0.600 inches

**Second Leg Slot Width:**

0.180 inches

**First Leg Thickness:**

0.090 inches

**Second Leg Thickness:**

0.090 inches

**First Leg Width:**

0.880 inches

**First Leg Distance Between Hole Centers Along Length:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.190 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 0.09 radians and 0.12 radians

**Product Name:**

Bracket, angle-attenuator

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, class 1a or class 3 military standard single treatment response

**Style Designator:**

Angle

**Fsc Application Data:**

Nha pn 11456678

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.