

View Online at <https://aerobasegroup.com/nsn/5340-01-492-4738>

**First Leg Length:**

2.000 inches

**Second Leg Length:**

2.500 inches

**End Application:**

2350-01-436-0005; armored reconnaissance-airborne assault vehicle: bradley

**Second Leg Width:**

0.5000 inches

**First Leg Hole Diameter:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.7500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.6250 inches

**Second Leg Slot Length:**

Between 0.960 inches and 1.020 inches

**Second Leg Slot Width:**

Between 0.480 inches and 0.500 inches

**First Leg Thickness:**

0.500 inches

**Second Leg Thickness:**

0.500 inches

**First Leg Width:**

0.5000 inches

**First Leg End Width:**

0.120 inches

**First Leg Distance Between Hole Centers Along Width:**

1.000 inches

**First Leg Distance Between Hole Centers Along Length:**

0.5000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.5000 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.4000 inches

**First Leg Style:**

Angle

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 5086

**Material Specification:**

Amst b221, 5086-h111 or h112 assn standard single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 3 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.