

View Online at <https://aerobasegroup.com/nsn/5340-01-492-4738>

First Leg Length:

2.000 inches

Second Leg Length:

2.500 inches

End Application:

2350-01-436-0005; armored reconnaissance-airborne assault vehicle: bradley

Second Leg Width:

0.5000 inches

First Leg Hole Diameter:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.7500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.6250 inches

Second Leg Slot Length:

Between 0.960 inches and 1.020 inches

Second Leg Slot Width:

Between 0.480 inches and 0.500 inches

First Leg Thickness:

0.500 inches

Second Leg Thickness:

0.500 inches

First Leg Width:

0.5000 inches

First Leg End Width:

0.120 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance Between Hole Centers Along Length:

0.5000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.5000 inches

First Leg Distance From Edge To Hole Center Along Length:

1.4000 inches

First Leg Style:

Angle

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 5086

Material Specification:

Amst b221, 5086-h111 or h112 assn standard single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.