

View Online at <https://aerobasegroup.com/nsn/5340-01-493-6439>

First Leg Length:

1.000 inches

Second Leg Length:

1.000 inches

End Application:

Mk 104 mod 3

Second Leg Width:

3.000 inches

Second Leg Corner Radius:

0.180 inches

First Leg Hole Diameter:

Between 0.215 inches and 0.232 inches

Second Leg Hole Diameter:

Between 0.192 inches and 0.199 inches

Second Leg Distance Between Hole Centers Along Width:

0.750 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.750 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.107 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

3.000 inches

First Leg Corner Radius:

0.180 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.000 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.562 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Made from aluminum alloy qq-a-200/8, temper t6; vertical leg has 4 holes drilled at 6 degrees 30 sec angle up from horizontal plane and spotfaced 0.500 inch; horizontal leg's 3 holes are counterbored 0.625 inch deep; horizontal leg is below vertical leg when mounted; both legs have a small lip on edge; see drawing for fabrication

Material:

Aluminum alloy

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0