## NSN 5340-01-493-7126

Snap-in Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-493-7126

3
Thread Class:
2b left internal (includes through thread)
Thread Direction:
Right-hand right external
Thread Length:
0.680 inches right external
Groove Diameter:
Between 0.405 inches and 0.415 inches
Groove Width:
0.260 inches
Length:
1.400 inches
Distance From End To Groove:
0.680 inches
Thready Qty Per Inch (tpi):
24 left internal (includes through thread)
Thread Size:
0.500 inches right external
Right Slot Width:
Between 0.126 inches and 0.156 inches
Right Slot Depth:
Between 0.188 inches and 0.218 inches
Right Projection Diameter:
Between 0.493 inches and 0.503 inches
Right Projection Length:
Between 0.280 inches and 0.300 inches
Special Features:
The locking slot for the forced inserted pellet islocated on the side of the shaft in the threaded area.
Material:
Nickel alloy insert
Material Specification:
Qq-n-281 federal specification single material response insert
Style Designator:
Left internal and right external thread
Thread Series Designator:
Unf left internal (includes through thread)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5340-01-493-7126

Snap-in Threaded Standoff - Page 2 of 2



Fiig:

A08900