

View Online at <https://aerobasegroup.com/nsn/5340-01-493-7868>

Mounting Hole Type:

Plain

First Leg Length:

Between 0.280 inches and 0.300 inches

Second Leg Length:

Between 0.700 inches and 0.740 inches

Second Leg Width:

Between 4.670 inches and 4.710 inches

Second Leg Hole Diameter:

Between 0.187 inches and 0.193 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

Between 2.120 inches and 2.130 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

Between 2.120 inches and 2.130 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.200 inches and 0.240 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.470 inches and 0.510 inches

First Leg Thickness:

Between 0.075 inches and 0.085 inches

Second Leg Thickness:

Between 0.075 inches and 0.085 inches

First Leg Width:

Between 4.670 inches and 4.710 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.080 radians

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Material:

Steel comp 1018

Material Specification:

Ast-108-69 assn standard all material responses

Surface Treatment:

Cadmium and primer and primer and primer epoxy

Surface Treatment Specification:

Qq-p-416 federal specification 1st treatment response and mil-c-22750 class 2 military specification 2nd treatment response and mil-p-23377 military specification 3rd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-22750 spec.