# NSN 5340-01-496-9753

Snap-in Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-496-9753

Th	rea	d (	CI	ass:

2b left internal (includes through thread)

### **Thread Direction:**

Right-hand left internal (includes through thread)

# Thread Length:

0.250 inches and 0.266 inches left internal (includes through thread)

#### **Hole Diameter:**

Between 0.150 inches and 0.153 inches

### Length:

Between 0.250 inches and 0.266 inches

### **End Application:**

5895-01-476-7819

### Thready Qty Per Inch (tpi):

40 left internal (includes through thread)

#### **Thread Size:**

0.112 inches left internal (includes through thread)

### **Right Projection Diameter:**

Between 0.185 inches and 0.188 inches

# **Right Projection Length:**

Between 0.102 inches and 0.108 inches

# **Special Features:**

Threaded end outside diameter is 0.250

### Material:

Copper alloy 360

# **Material Specification:**

Qq-b-626, comp 22 federal specification single material response

# **Surface Treatment:**

Tin

### **Surface Treatment Specification:**

Mil-t-10727, type 1 military specification single treatment response

# Style Designator:

Internally threaded full length

# **Thread Series Designator:**

Unc left internal (includes through thread)

### Shelf Life:

N/a

## **Unit Of Measure:**

--

# Demilitarization:

No

# Fiig:

A08900

# NSN 5340-01-496-9753

Snap-in Threaded Standoff - Page 2 of 2



Mil-std (military Standard):

Mil-t-10727 spec.