

View Online at <https://aerobasegroup.com/nsn/5340-01-497-8545>

Mounting Hole Type:

Plain

First Leg Length:

1.500 inches

Second Leg Length:

2.000 inches

Second Leg Width:

Between 19.190 inches and 19.310 inches

First Leg Slot Length:

0.810 inches

First Leg Slot Width:

Between 0.311 inches and 0.322 inches

First Leg Thickness:

0.188 inches

Second Leg Thickness:

0.188 inches

First Leg Width:

Between 19.190 inches and 19.310 inches

First Leg Distance Between First And Second Hole Centers Along Width:

5.750 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

5.750 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.780 inches and 0.900 inches

First Leg Distance From Edge To Hole Center Along Length:

0.625 inches

First Leg Distance Between Third And Fourth Hole Centers Along Width:

5.750 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

4 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

No hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Mrc mdcl reflects a supercession of qq-a-200; mrc stdc reflects a supercession of mil-c-22750; epoxy color finish is It green

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Astm-b221-2000 national specification all material responses

Surface Treatment:

Primer epoxy and plastic epoxy

Surface Treatment Specification:

Mil-prf-22750 military specification all treatment responses

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-prf-22750 spec.