

View Online at <https://aerobasegroup.com/nsn/5340-01-497-8545>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.500 inches

**Second Leg Length:**

2.000 inches

**Second Leg Width:**

Between 19.190 inches and 19.310 inches

**First Leg Slot Length:**

0.810 inches

**First Leg Slot Width:**

Between 0.311 inches and 0.322 inches

**First Leg Thickness:**

0.188 inches

**Second Leg Thickness:**

0.188 inches

**First Leg Width:**

Between 19.190 inches and 19.310 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

5.750 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

5.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.780 inches and 0.900 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.625 inches

**First Leg Distance Between Third And Fourth Hole Centers Along Width:**

5.750 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

4 slots

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

No hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Mrc mdcl reflects a supercession of qq-a-200; mrc stdc reflects a supercession of mil-c-22750; epoxy color finish is It green

**Material:**

Aluminum alloy 5083 or aluminum alloy 5086

**Material Specification:**

Astm-b221-2000 national specification all material responses

**Surface Treatment:**

Primer epoxy and plastic epoxy

**Surface Treatment Specification:**

Mil-prf-22750 military specification all treatment responses

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-prf-22750 spec.