NSN 5340-01-498-0666

Double Angle Bracket - Page 1 of 2

Mounting Hole Type:



View Online at https://aerobasegroup.com/nsn/5340-01-498-0666

Plain
First Leg Length:
0.910 inches
Second Leg Length:
1.500 inches
End Application:
2350-01-455-3174
Second Leg Width:
Between 4.190 inches and 4.310 inches
Second Leg End Width:
Between 3.690 inches and 3.810 inches
First Leg Hole Diameter:
Between 0.374 inches and 0.385 inches
Second Leg Hole Diameter:
Between 0.195 inches and 0.206 inches
Second Leg Distance Between Hole Centers Along Width:
1.275 inches
Second Leg Distance From Edge To Hole Center Along Width:
2.350 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.500 inches
First Leg Thickness:
0.125 inches
Second Leg Thickness:
0.125 inches
Center Section Height:
Between 1.450 inches and 1.850 inches
Center Section Width:
Between 4.190 inches and 4.310 inches
Center Section Thickness:
0.125 inches
First Leg Width:
Between 4.190 inches and 4.310 inches
First Leg Distance Between Hole Centers Along Width:
1.560 inches
First Leg Distance From Edge To Hole Center Along Width:
1.940 inches
First Leg Distance From Edge To Hole Center Along Length:
0.313 inches
First Leg Style:
Square

NSN 5340-01-498-0666Double Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Chamfered ends
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
0.13 radians
Second Leg Angle:
0.13 radians
Second Leg Chamfer Angle:
Between 45.0 degrees and 50.0 degrees
Special Features:
This item is the exact opposite of p/n 12478972-3; 2nd "hole" on 1st leg is actually aa slot 0.375 in (along width) by 0.50 in (along length)
and centered 0.38 in from edge along length; finish: color is 383 green, chip no. 34094 of fed-std-595; omit prime and paint from holes;
dimensiona; limits and surface texture apply without coating
Material:
Aluminum alloy 6061
Material Specification:
Astm b209m national specification all material responses
Surface Treatment:
Chromate and primer epoxy and plastic polyurethane
Surface Treatment Specification:
Mil-std-171 military standard 1st treatment response and fed-std-595 federal standard 2nd treatment response
Style Designator:
Adjacent angles
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A042a0
Mil-std (military Standard):
Mil-std-171 spec.