

View Online at <https://aerobasegroup.com/nsn/5340-01-498-9726>

**Mounting Hole Type:**

Countersunk

**First Leg Length:**

10.0 millimeters

**Second Leg Length:**

34.0 millimeters

**End Application:**

Elect test equip - gpete

**Second Leg Width:**

92.0 millimeters

**First Leg Hole Diameter:**

2.8 millimeters

**Second Leg Hole Diameter:**

2.8 millimeters

**Second Leg Distance Between Hole Centers Along Width:**

56.5 millimeters

**Second Leg Distance Between First And Second Hole Centers Along Width:**

10.8 millimeters

**Second Leg Distance Between Second And Third Hole Centers Along Width:**

10.8 millimeters

**Second Leg Distance From Edge To Hole Center Along Width:**

15.8 millimeters

**Second Leg Distance From Edge To Hole Center Along Length:**

17.0 millimeters

**First Leg Thickness:**

0.0018 millimeters

**Second Leg Thickness:**

0.0018 millimeters

**First Leg Width:**

10.0 millimeters

**First Leg Distance From Edge To Hole Center Along Width:**

3.5 millimeters

**First Leg Distance From Edge To Hole Center Along Length:**

5.0 millimeters

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Product Name:**

Reg. Bkt.

**Special Features:**

First leg refers to 2 10x10 tabs on each end of bracket; second leg's 4 holes are c'sk 90 degrees x 5.7; second leg also has 3 holes 9.25 diam (to fit m3 pem), 2 are 5.0 from each short side and 17.0 from long edge, third hole is 29.0 from angle edge and 46.0 from side edge

**Material:**

Aluminum

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0