

View Online at <https://aerobasegroup.com/nsn/5340-01-498-9726>

Mounting Hole Type:

Countersunk

First Leg Length:

10.0 millimeters

Second Leg Length:

34.0 millimeters

End Application:

Elect test equip - gpete

Second Leg Width:

92.0 millimeters

First Leg Hole Diameter:

2.8 millimeters

Second Leg Hole Diameter:

2.8 millimeters

Second Leg Distance Between Hole Centers Along Width:

56.5 millimeters

Second Leg Distance Between First And Second Hole Centers Along Width:

10.8 millimeters

Second Leg Distance Between Second And Third Hole Centers Along Width:

10.8 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

15.8 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

17.0 millimeters

First Leg Thickness:

0.0018 millimeters

Second Leg Thickness:

0.0018 millimeters

First Leg Width:

10.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

3.5 millimeters

First Leg Distance From Edge To Hole Center Along Length:

5.0 millimeters

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Product Name:

Reg. Bkt.

Special Features:

First leg refers to 2 10x10 tabs on each end of bracket; second leg's 4 holes are c'sk 90 degrees x 5.7; second leg also has 3 holes 9.25 diam (to fit m3 pem), 2 are 5.0 from each short side and 17.0 from long edge, third hole is 29.0 from angle edge and 46.0 from side edge

Material:

Aluminum

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0