Angle Bracket - Page 1 of 2





Mounting Hole Type:

Plain

First Leg Length:

1.880 inches

Second Leg Length:

2.880 inches

End Application:

HMMW-V;-232-0014

Second Leg Width:

7.750 inches

First Leg Slot Length:

0.540 inches

First Leg Slot Width:

0.290 inches

Second Leg Hole Diameter:

Between 0.295 inches and 0.300 inches

Second Leg Distance Between Hole Centers Along Width:

5.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.880 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.625 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

7.750 inches

First Leg Distance Between First And Second Hole Centers Along Width:

5.000 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

0.870 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

0.875 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

3 slots

Second Leg Style:

Cut out

NSN 5340-01-499-1716

Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees First Leg Cutout Length: 1.310 inches First Leg Cutout Width: 3.500 inches Second Leg Cutout Length: 2.880 inches Second Leg Cutout Width: 3.500 inches **Product Name:** Mtg angle, cover, driver's side, frt **Special Features:** 2 upset nuts, 0.190-32 Material: Aluminum alloy 6061 **Surface Treatment:** Primer and paint Style Designator: Angle Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A042a0