

View Online at <https://aerobasegroup.com/nsn/5340-01-499-2472>

Mounting Hole Type:

Plain

First Leg Length:

3.750 inches

Second Leg Length:

4.000 inches

End Application:

BRAD-LE-Y;2-3500

Second Leg Width:

3.000 inches

Second Leg End Width:

2.500 inches

First Leg Slot Length:

0.500 inches

First Leg Slot Width:

Between 0.210 inches and 0.230 inches

Second Leg Hole Diameter:

Between 0.490 inches and 0.510 inches

Second Leg Distance Between Hole Centers Along Width:

1.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.745 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Thickness:

0.190 inches

Second Leg Thickness:

0.190 inches

First Leg Width:

4.250 inches

First Leg End Width:

3.750 inches

First Leg Distance Between Hole Centers Along Width:

3.125 inches

First Leg Distance From Edge To Hole Center Along Width:

0.563 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Product Name:

Annunciator bracket

Special Features:

Xlonge (vertical) leg has third hole 1.000 inch in diameter, centered 0.745 from left edge and 0.745 from bend; shorter(horizontal) leg has 1.250 x1.250 inch cut out with corner rounded to radius of 0.250 on right corner at the bend

Material:

Aluminum alloy 5086 or aluminum alloy 5052

Material Specification:

Astm b209, alloy 5086-h32 or h116 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0