

View Online at <https://aerobasegroup.com/nsn/5340-01-499-2472>

**Mounting Hole Type:**

Plain

**First Leg Length:**

3.750 inches

**Second Leg Length:**

4.000 inches

**End Application:**

BRAD-LE-Y;2-3500

**Second Leg Width:**

3.000 inches

**Second Leg End Width:**

2.500 inches

**First Leg Slot Length:**

0.500 inches

**First Leg Slot Width:**

Between 0.210 inches and 0.230 inches

**Second Leg Hole Diameter:**

Between 0.490 inches and 0.510 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.745 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.750 inches

**First Leg Thickness:**

0.190 inches

**Second Leg Thickness:**

0.190 inches

**First Leg Width:**

4.250 inches

**First Leg End Width:**

3.750 inches

**First Leg Distance Between Hole Centers Along Width:**

3.125 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.563 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**First Leg Chamfer Angle:**

45.0 degrees

**Second Leg Chamfer Angle:**

45.0 degrees

**Product Name:**

Annunciator bracket

**Special Features:**

Xlonge (vertical) leg has third hole 1.000 inch in diameter, centered 0.745 from left edge and 0.745 from bend; shorter(horizontal) leg has 1.250 x1.250 inch cut out with corner rounded to radius of 0.250 on right corner at the bend

**Material:**

Aluminum alloy 5086 or aluminum alloy 5052

**Material Specification:**

Astm b209, alloy 5086-h32 or h116 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0