

View Online at <https://aerobasegroup.com/nsn/5340-01-499-3141>

Mounting Hole Type:

Plain

First Leg Length:

7.020 inches

Second Leg Length:

17.650 inches

Furnished Items (non-core):

Includes gussets for side and front

End Application:

BRAD-LE-Y;2-3500

Second Leg Width:

17.650 inches

Second Leg End Width:

15.268 inches

First Leg Slot Length:

0.750 inches

First Leg Slot Width:

Between 0.437 inches and 0.500 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

2.750 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

2.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.610 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.380 inches

Second Leg Slot Length:

0.750 inches

Second Leg Slot Width:

Between 0.437 inches and 0.500 inches

Second Leg Distance Between Third And Fourth Hole Centers Along Width:

2.750 inches

First Leg Thickness:

0.500 inches

Second Leg Thickness:

0.500 inches

First Leg Width:

15.120 inches

First Leg End Width:

9.130 inches

First Leg Distance Between Hole Centers Along Width:

6.875 inches

First Leg Distance Between Hole Centers Along Length:

3.125 inches

First Leg Distance From Edge To Hole Center Along Width:

6.370 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

4 slots

Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

5 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Offset Angle:

15.0 degrees

Err Default:

Err default

Product Name:

Bracket assembly, display

Special Features:

Aslots on longer leg are centered crosswise on line 0.380 from left edge; there are 3 slots of same size centered 1.734 from right edge and 1.257, 3.257 and 5.257 inches from open end of bracket

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Astm 209, alloy 5083-h321 except 24, 000 psi min yield strength and 40, 000 psi min tensile strength or alloy 5086-h32 or h-116 assn standard single material response

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0