

View Online at <https://aerobasegroup.com/nsn/5340-01-501-0054>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.800 inches

**Second Leg Length:**

1.200 inches

**End Application:**

5895-01-490-7035

**Second Leg Width:**

1.200 inches

**Second Leg Corner Radius:**

0.130 inches

**First Leg Slot Length:**

0.360 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.125 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.440 inches

**Second Leg Slot Length:**

1.810 inches

**Second Leg Slot Width:**

0.160 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

2.250 inches

**First Leg Corner Radius:**

0.130 inches

**First Leg Distance Between Hole Centers Along Width:**

1.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.310 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Product Name:**

Locking bracket

**Special Features:**

Radius of each end of both slots on first leg is 0.125 in

**Material:**

Aluminum alloy 5052

**Material Specification:**

Astm-b209-2002 national specification single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0