## NSN 5340-01-502-5900

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-502-5900

Second Leg Length:
1.620 inches
End Application:
Cp-1273/upx-2
Second Leg Width:
2.750 inches
First Leg Hole Diameter:
0.263 inches
Second Leg Hole Diameter:
0.201 inches
Second Leg Distance Between Hole Centers Along Width:
2.120 inches
Second Leg Distance Between Hole Centers Along Length:
0.9437 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.310 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.183 inches
First Leg Thickness:
0.090 inches
Second Leg Thickness:
0.090 inches
Center Section Height:
2.400 inches
Center Section Width:
2.750 inches
Center Section Thickness:
0.090 inches
First Leg Width:
2.750 inches
First Leg Distance Between Hole Centers Along Width:
1.750 inches
First Leg Distance From Edge To Hole Center Along Width:
0.500 inches
First Leg Distance From Edge To Hole Center Along Length:
0.750 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Corner radius

## NSN 5340-01-502-5900

Double Angle Bracket - Page 2 of 2

A042a0



Second Leg Hole Arrangement Style:
Four holes
Second Leg Relationship To First Leg:
Not identical
Special Features:
This item includes p/n422190-98 which is an insulator and which measures 2.750 in (along width) by 1.040 in (along length), and its holes
are exact match to those on first leg of item
Material:
Aluminum alloy 6061
Style Designator:
Adjacent angles
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: