NSN 5340-01-503-1588

Catch Strike - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-503-1588

Overall Length: 4.150 inches Overall Width: 2.000 inches Mounting Hole Diameter: Between 0.189 inches and 0.195 inches Hole Quantity: 3 Product Name: Catch, right side latch-door latch mechanism Thickness: 0.500 inches Special Features: The leg which extends downward measures 1.62 in long, 1.000 in wide, and is 0.25 in thick; the distance from base to bottom of stril groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in from edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Liffe: N/a Unit Of Measure:	
Overall Width: 2.000 inches Mounting Hole Diameter: Between 0.189 inches and 0.195 inches Hole Quantity: 3 Product Name: Catch, right side latch-door latch mechanism Thickness: 0.500 inches Special Features: The leg which extends downward measures 1.62 in long, 1.000 in wide, and is 0.25 in thick; the distance from base to bottom of stril groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in from edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
2.000 inches Mounting Hole Diameter: Between 0.189 inches and 0.195 inches Hole Quantity: 3 Product Name: Catch, right side latch-door latch mechanism Thickness: 0.500 inches Special Features: The leg which extends downward measures 1.62 in long, 1.000 in wide, and is 0.25 in thick; the distance from base to bottom of strile groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in from edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Mounting Hole Diameter: Between 0.189 inches and 0.195 inches Hole Quantity: 3 Product Name: Catch, right side latch-door latch mechanism Thickness: 0.500 inches Special Features: The leg which extends downward measures 1.62 in long, 1.000 in wide, and is 0.25 in thick; the distance from base to bottom of strik groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in from edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Between 0.189 inches and 0.195 inches Hole Quantity: 3 Product Name: Catch, right side latch-door latch mechanism Thickness: 0.500 inches Special Features: The leg which extends downward measures 1.62 in long, 1.000 in wide, and is 0.25 in thick; the distance from base to bottom of strik groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in from edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Hole Quantity: 3 Product Name: Catch, right side latch-door latch mechanism Thickness: 0.500 inches Special Features: The leg which extends downward measures 1.62 in long, 1.000 in wide, and is 0.25 in thick; the distance from base to bottom of strik groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in from edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Product Name: Catch, right side latch-door latch mechanism Thickness: 0.500 inches Special Features: The leg which extends downward measures 1.62 in long, 1.000 in wide, and is 0.25 in thick; the distance from base to bottom of strik groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in from edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Product Name: Catch, right side latch-door latch mechanism Thickness: 0.500 inches Special Features: The leg which extends downward measures 1.62 in long, 1.000 in wide, and is 0.25 in thick; the distance from base to bottom of strik groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in from edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Catch, right side latch-door latch mechanism Thickness: 0.500 inches Special Features: The leg which extends downward measures 1.62 in long, 1.000 in wide, and is 0.25 in thick; the distance from base to bottom of strik groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in from edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Thickness: 0.500 inches Special Features: The leg which extends downward measures 1.62 in long, 1.000 in wide, and is 0.25 in thick; the distance from base to bottom of strik groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in from edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Special Features: The leg which extends downward measures 1.62 in long, 1.000 in wide, and is 0.25 in thick; the distance from base to bottom of strik groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in from edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Special Features: The leg which extends downward measures 1.62 in long, 1.000 in wide, and is 0.25 in thick; the distance from base to bottom of strik groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in from edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
The leg which extends downward measures 1.62 in long, 1.000 in wide, and is 0.25 in thick; the distance from base to bottom of strik groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in from edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
groove is 0.514 in; a 0.190 in diameter threaded hole, fully-threaded at 0.400 in deep (32 threads/inch, unf-2a) is located 1.00 in fron edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
edge along width and 0.215 in along heighth Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	æ
Height: 1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	า righ
1.000 inches Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Material: Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Titanium alloy Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Material Specification: Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Astm b265-1999e1 national specification single material response Style Designator: Surface Shelf Life: N/a	
Style Designator: Surface Shelf Life: N/a	
Surface Shelf Life: N/a	
Shelf Life: N/a	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A10600	