NSN 5340-01-504-7339

Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-504-7339 **Thread Class:** 2b left internal (includes through thread) **Thread Direction:** Right-hand right external Thread Length: 0.450 inches left internal (includes through thread) **Groove Diameter:** Between 0.350 inches and 0.360 inches Flange Thickness: 0.187 inches Diameter: 0.562 inches Length: 0.438 inches Flange Width Across Flats: 0.562 inches **End Application:** Kc135 gatm a **Groove Radius:** 0.032 inches **Cross-sectional Shape:** Round Thready Qty Per Inch (tpi): 24 left internal (includes through thread) **Thread Size:** 0.438 inches right external **Right Projection Diameter:** Between 0.350 inches and 0.360 inches **Right Projection Length:** 0.625 inches **Special Features:** Controlling agency item name is adapter-lightning arrestor Material: Copper alloy **Material Specification:** Astm-b16/b16m-2000 national specification all material responses **Style Designator:** Projection and flange left internal and right external thread **Thread Series Designator:** Unf right external

N/a

Shelf Life:

NSN 5340-01-504-7339

Spacing Threaded Standoff - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A08900