

View Online at <https://aerobasegroup.com/nsn/5340-01-506-5147>

Mounting Hole Type:

Counterbored

First Leg Length:

2.750 inches

Second Leg Length:

2.000 inches

End Application:

W/s: aircraft, tomcat f-14

Second Leg Width:

4.578 inches

Second Leg End Width:

1.000 inches

First Leg Hole Diameter:

Between 0.122 inches and 0.130 inches

Second Leg Hole Diameter:

0.194 inches

Second Leg Distance Between Lower Hole Centers Along Width:

1.000 inches

Second Leg Distance Between Hole Centers Along Length:

2.310 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.500 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

4.578 inches

First Leg Distance Between Hole Centers Along Width:

0.719 inches

First Leg Distance Between Hole Centers Along Length:

0.719 inches

First Leg Distance From Edge To Hole Center Along Width:

0.619 inches

First Leg Distance From Edge To Hole Center Along Length:

0.140 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Product Name:

Bay 1 stowage bracket

Special Features:

Zleg one has 8 additional holes (with same diameter) placed between already mentioned holes and the angle; leg two has one additional hole (diameter of 0.187 inches) placed 0.750 inches above far right hole already mentioned and angle

Material:

Aluminum alloy 6061

Material Specification:

Sae-ams-qq-a-250/11, type 4 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, cl 1 military specification 4th treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.