NSN 5340-01-506-5147

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-506-5147

Mounting Hole Type:
Counterbored
First Leg Length:
2.750 inches
Second Leg Length:
2.000 inches
End Application:
W/s: aircraft, tomcat f-14
Second Leg Width:
4.578 inches
Second Leg End Width:
1.000 inches
First Leg Hole Diameter:
Between 0.122 inches and 0.130 inches
Second Leg Hole Diameter:
0.194 inches
Second Leg Distance Between Lower Hole Centers Along Width:
1.000 inches
Second Leg Distance Between Hole Centers Along Length:
2.310 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Length:
1.500 inches
First Leg Thickness:
0.125 inches
Second Leg Thickness:
0.125 inches
First Leg Width:
4.578 inches
First Leg Distance Between Hole Centers Along Width:
0.719 inches
First Leg Distance Between Hole Centers Along Length:
0.719 inches
First Leg Distance From Edge To Hole Center Along Width:
0.619 inches
First Leg Distance From Edge To Hole Center Along Length:
0.140 inches
First Leg Style:
Square

NSN 5340-01-506-5147 Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style:
Four holes
Second Leg Style:
Angle
Second Leg Hole Arrangement Style:
Three holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Product Name:
Bay 1 stowage bracket
Special Features:
Zleg one has 8 additional holes (with same diameter) placed between already mentioned holes and the angle; leg two has one additional
nole (diameter of 0.187 inches) placed 0.750 inches above far right hole already mentioned and angle
Material:
Aluminum alloy 6061
Material Specification:
Sae-ams-qq-a-250/11, type 4 assn standard single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2, cl 1 military specification 4th treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Filg:
A042a0
Mil-std (military Standard):
Mil-a-8625 spec.