

View Online at <https://aerobasegroup.com/nsn/5340-01-509-0380>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.600 inches

**Second Leg Length:**

0.600 inches

**Second Leg Width:**

1.380 inches

**Second Leg End Width:**

1.120 inches

**First Leg Hole Diameter:**

0.144 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.460 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.460 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.256 inches

**Second Leg Slot Length:**

0.250 inches

**Second Leg Slot Width:**

0.188 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

1.380 inches

**First Leg End Width:**

1.120 inches

**First Leg Distance Between Hole Centers Along Width:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.190 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.230 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

0.015 radians

**First Leg Chamfer Angle:**

Between 43.0 degrees and 47.0 degrees

**Second Leg Chamfer Angle:**

Between 43.0 degrees and 47.0 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

Astm-b308/b308m-2002 national specification single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0