

View Online at <https://aerobasegroup.com/nsn/5340-01-509-1472>

Cross Sectional Shape:

Recess, same shape as the periphery

Hole Diameter:

Between 0.248 inches and 0.255 inches

Flange Thickness:

0.100 inches

Outside Diameter:

2.850 inches

Edge Shape:

Round, no holes

First Recess Inside Height:

3.150 inches

Body Thickness:

0.100 inches

Securing Device Type:

Special

Mounting Opening Shape Style:

Unthreaded hole

End Application:

Drive, assembly, s

Special Features:

Has 2 holes centered 1.175 from bottom/open edge, equally spaced around circumference; has neoprene antivibration pads: one 1.00x1.00x0.75 centered on underside of top and two 2.00x1.00x0.125 centered lengthwise above holes with bottom edges 1.50 from bottom edge of cover

Material:

Aluminum alloy 6061 and rubber synthetic

Material Specification:

Astm b21, t651 assn standard 1st material response and astm d2000 2bc 415 a14 b14 c12 eo14 f17 assn standard 2nd material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type ii, class 2, black military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-a-8625 spec.