

View Online at <https://aerobasegroup.com/nsn/5340-01-509-4712>

Mounting Hole Type:

Plain

First Leg Length:

9.500 inches

Second Leg Length:

9.810 inches

Second Leg Width:

1.480 inches

Second Leg Corner Radius:

0.120 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.740 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.860 inches

Second Leg Distance Between First And Second Hole Centers Along Length:

3.100 inches

Second Leg Distance Between Second And Third Hole Centers Along Length:

1.150 inches

Second Leg Slot Length:

0.781 inches

Second Leg Slot Width:

0.281 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

4.500 inches

First Leg Corner Radius:

0.120 inches

First Leg Distance Between Hole Centers Along Width:

3.480 inches

First Leg Distance Between Hole Centers Along Length:

4.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.520 inches

First Leg Distance From Edge To Hole Center Along Length:

0.507 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

3 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Product Name:

Bracket, 2 way valve

Special Features:

Has two additional slots directly in line with others on leg 2 center positioned 1.750 inches and 3.750 inches from slot 3 respectfully; portion of bracket beginning at 1.480 inches from outside corner of where leg one and two are joined and extending 2.730 inches down leg one is angled back to a distance of 0.880 inches

Material:

Aluminum alloy 5052

Material Specification:

Astm-8209, temper h32 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0