NSN 5340-01-509-4768

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-509-4768 First Leg Length: 0.940 inches Second Leg Length: 3.000 inches Second Leg Width: 12.000 inches **Second Leg Corner Radius:** 0.500 inches First Leg Hole Diameter: 0.369 inches Second Leg Hole Diameter: 1.703 inches Second Leg Distance Between Hole Centers Along Width: 9.000 inches Second Leg Distance Between First And Second Hole Centers Along Width: 3.000 inches Second Leg Distance Between Second And Third Hole Centers Along Width: 3.000 inches Second Leg Distance From Edge To Hole Center Along Width: 1.500 inches Second Leg Distance From Edge To Hole Center Along Length: 1.250 inches First Leg Thickness: 0.090 inches **Second Leg Thickness:** 0.090 inches First Leg Width: 12.000 inches First Leg Distance Between First And Second Hole Centers Along Width: 4.500 inches First Leg Distance Between Second And Third Hole Centers Along Width: 4.500 inches First Leg Distance From Edge To Hole Center Along Width: 1.470 inches First Leg Distance From Edge To Hole Center Along Length: 0.540 inches First Leg Style: Square First Leg Hole Arrangement Style: Three holes

Second Leg Style:

Corner radius

NSN 5340-01-509-4768 Angle Bracket - Page 2 of 2



| Second Leg Hole Arrangement Style: |
|--|
| Four holes |
| Second Leg Relationship To First Leg: |
| Not identical |
| First Leg Angle: |
| 90.0 degrees |
| Product Name: |
| Connector bracket, icad desktop |
| Special Features: |
| Has 16 additional mounting holes on leg 2, 4 each around holes already listed (forming a square box look) spaced equally at 1.500 inches |
| apart along length edge beginning at 0.750 inches and along width edge beginning at 0.500 inches. |
| Material: |
| Aluminum alloy 5052 |
| Material Specification: |
| Astm-b209, temper h32 assn standard single material response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A042a0 |
| |
| |