

View Online at <https://aerobasegroup.com/nsn/5340-01-509-4797>

Mounting Hole Type:

Plain

First Leg Length:

0.750 inches

Second Leg Length:

0.530 inches

Second Leg Width:

5.180 inches

First Leg Hole Diameter:

Between 0.196 inches and 0.200 inches

Second Leg Hole Diameter:

Between 0.406 inches and 0.409 inches

Second Leg Distance Between Hole Centers Along Width:

4.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.584 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

1.800 inches

Center Section Width:

5.180 inches

Center Section Thickness:

0.125 inches

First Leg Width:

5.180 inches

First Leg Corner Radius:

0.125 inches

First Leg Distance Between Hole Centers Along Width:

4.395 inches

First Leg Distance From Edge To Hole Center Along Width:

0.281 inches

First Leg Distance From Edge To Hole Center Along Length:

0.266 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

Second Leg Angle:

90.0 degrees

First Leg Offset Angle:

90.0 degrees

Second Leg Offset Angle:

82.0 degrees

Product Name:

Bracket, mounging, middle

Special Features:

Surface treatment: chemical conversion coating

Material:

Aluminum alloy 5052

Material Specification:

Astm b209, temper h32 assn standard single material response

Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

Style Designator:

Offset double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.