

View Online at <https://aerobasegroup.com/nsn/5340-01-509-4910>

**First Leg Length:**

2.750 inches

**Second Leg Length:**

8.000 inches

**Second Leg Width:**

4.000 inches

**Second Leg Corner Radius:**

0.500 inches

**First Leg Hole Diameter:**

0.250 inches

**Second Leg Hole Diameter:**

Between 1.490 inches and 1.510 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.625 inches

**Second Leg Distance Between Hole Centers Along Length:**

3.125 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.812 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.938 inches

**First Leg Thickness:**

0.380 inches

**Second Leg Thickness:**

Between 0.125 inches and 0.380 inches

**First Leg Width:**

3.515 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

1.250 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

1.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.255 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.342 inches

**First Leg Style:**

Cut out

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**First Leg Cutout Length:**

0.750 inches

**First Leg Cutout Width:**

0.750 inches

**Product Name:**

Bracket, manifold mounting

**Special Features:**

Holes on first leg are threaded .250-20 unc-2b and cutout starts 1.51 from top edge; second leg has 2 additional holes, 1.500 in diam, centered 2.500 from open end and 1.00 from either side; second leg tapers from 0.38 for 2.94 inches from angle to 0.125 for last 4.560 inches

**Material:**

Titanium alloy

**Material Specification:**

Mil-t-9046, comp 6al/4v military specification single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-t-9046 spec.