

View Online at <https://aerobasegroup.com/nsn/5340-01-509-4910>

First Leg Length:

2.750 inches

Second Leg Length:

8.000 inches

Second Leg Width:

4.000 inches

Second Leg Corner Radius:

0.500 inches

First Leg Hole Diameter:

0.250 inches

Second Leg Hole Diameter:

Between 1.490 inches and 1.510 inches

Second Leg Distance Between Hole Centers Along Width:

2.625 inches

Second Leg Distance Between Hole Centers Along Length:

3.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.812 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.938 inches

First Leg Thickness:

0.380 inches

Second Leg Thickness:

Between 0.125 inches and 0.380 inches

First Leg Width:

3.515 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.250 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.255 inches

First Leg Distance From Edge To Hole Center Along Length:

0.342 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Cutout Length:

0.750 inches

First Leg Cutout Width:

0.750 inches

Product Name:

Bracket, manifold mounting

Special Features:

Holes on first leg are threaded .250-20 unc-2b and cutout starts 1.51 from top edge; second leg has 2 additional holes, 1.500 in diam, centered 2.500 from open end and 1.00 from either side; second leg tapers from 0.38 for 2.94 inches from angle to 0.125 for last 4.560 inches

Material:

Titanium alloy

Material Specification:

Mil-t-9046, comp 6al/4v military specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-t-9046 spec.