

View Online at <https://aerobasegroup.com/nsn/5340-01-509-5365>

Mounting Hole Type:

Plain

First Leg Length:

0.781 inches

Second Leg Length:

8.750 inches

Second Leg Width:

Between 18.540 inches and 18.570 inches

First Leg Hole Diameter:

Between 0.201 inches and 0.207 inches

Second Leg Hole Diameter:

Between 0.201 inches and 0.207 inches

Second Leg Distance Between Hole Centers Along Width:

5.000 inches

Second Leg Distance Between Hole Centers Along Length:

1.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.063 inches

Second Leg Distance From Edge To Hole Center Along Length:

3.358 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

Between 18.540 inches and 18.570 inches

First Leg Distance Between Hole Centers Along Width:

10.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.906 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

4.888 inches

First Leg Distance From Edge To Hole Center Along Width:

3.206 inches

First Leg Distance From Edge To Hole Center Along Length:

0.094 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Product Name:

Bracket, lower sonar, center rack

Special Features:

First leg has 3 slots, 0.500 w, open on bottom edge; 2nd leg has another row of holes with same dia. As first 2 rows, centered 1.063 in. From rt edge and 4.266 and 5.391 inches from top edge; 2nd leg has 2 large cutouts: an oval, 3.000 in. W x 5.500 in. H, centered between center and right rows of holes, and a rectangle with rounded corners, 5.000 in. W x 5.500 in. H, centered between the center and left rows of holes; 2nd leg has a lip with 4 holes, 1.200 in. W x 8.750 in. L along the underside of right edge and a lip with one hole .550 in. W x 2.250 in. L, flush with front edge, along left edge of bracket

Material:

Aluminum alloy 5052

Material Specification:

Astm b209, temper h32 assn standard single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.