

View Online at <https://aerobasegroup.com/nsn/5340-01-509-5383>

Mounting Hole Type:

Plain

First Leg Length:

3.090 inches

Second Leg Length:

1.000 inches

Furnished Items (non-core):

Nut, self-clinching, non locking

Second Leg Width:

1.000 inches

Second Leg Corner Radius:

0.130 inches

First Leg Hole Diameter:

0.406 inches

Second Leg Distance Between Hole Centers Along Length:

2.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

Second Leg Slot Length:

0.470 inches

Second Leg Slot Width:

0.219 inches

First Leg Thickness:

0.188 inches

Second Leg Thickness:

0.313 inches

Center Section Height:

3.160 inches

Center Section Width:

2.250 inches

Center Section Thickness:

0.188 inches

First Leg Width:

1.000 inches

First Leg Corner Radius:

0.250 inches

First Leg End Width:

2.250 inches

First Leg Distance Between Lower Hole Centers Along Width:

1.500 inches

First Leg Distance Between Hole Centers Along Length:

1.750 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Radius foot

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Product Name:

Arm, bracket, center rack

Special Features:

Second leg has an extended portion which only has one radial corner

Material:

Aluminum alloy 5052 and rubber neoprene

Material Specification:

Astm-b209, temper h32 assn standard 1st material response and mil-c-1149, t1, cl1 military specification 1st material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-1149 spec.