

View Online at <https://aerobasegroup.com/nsn/5340-01-509-6344>

**Mounting Hole Type:**

Threaded

**First Leg Length:**

3.000 inches

**Second Leg Length:**

8.000 inches

**Second Leg Width:**

4.000 inches

**Second Leg End Width:**

3.000 inches

**First Leg Slot Length:**

0.875 inches

**First Leg Slot Width:**

0.437 inches

**Second Leg Hole Diameter:**

0.375 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.000 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.875 inches

**First Leg Thickness:**

0.500 inches

**Second Leg Thickness:**

0.500 inches

**First Leg Width:**

6.000 inches

**First Leg End Width:**

5.000 inches

**First Leg Distance Between Hole Centers Along Width:**

3.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.750 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

45.0 degrees

**First Leg Chamfer Angle:**

45.0 degrees

**Second Leg Chamfer Angle:**

45.0 degrees

**Special Features:**

First leg has all 4 corners chamfered .50 x .50; second leg's mounting holes are .375-16 unc-2b

**Material:**

Titanium alloy

**Material Specification:**

Mil-t-9046, comp ab-2, 6al-4 (eli) , cond annealed military specification single material response

**Surface Treatment:**

Primer and paint

**Surface Treatment Specification:**

Mil-p-24441/20 military specification 1st treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-t-9046 spec.