

View Online at <https://aerobasegroup.com/nsn/5340-01-509-6344>

Mounting Hole Type:

Threaded

First Leg Length:

3.000 inches

Second Leg Length:

8.000 inches

Second Leg Width:

4.000 inches

Second Leg End Width:

3.000 inches

First Leg Slot Length:

0.875 inches

First Leg Slot Width:

0.437 inches

Second Leg Hole Diameter:

0.375 inches

Second Leg Distance Between Hole Centers Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.875 inches

First Leg Thickness:

0.500 inches

Second Leg Thickness:

0.500 inches

First Leg Width:

6.000 inches

First Leg End Width:

5.000 inches

First Leg Distance Between Hole Centers Along Width:

3.500 inches

First Leg Distance From Edge To Hole Center Along Width:

1.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

45.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

First leg has all 4 corners chamfered .50 x .50; second leg's mounting holes are .375-16 unc-2b

Material:

Titanium alloy

Material Specification:

Mil-t-9046, comp ab-2, 6al-4 (eli) , cond annealed military specification single material response

Surface Treatment:

Primer and paint

Surface Treatment Specification:

Mil-p-24441/20 military specification 1st treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-t-9046 spec.