

View Online at <https://aerobasegroup.com/nsn/5340-01-509-6396>

First Leg Length:

2.880 inches

Second Leg Length:

4.750 inches

Second Leg Width:

5.630 inches

Second Leg End Width:

4.870 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

2.000 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

3.246 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.119 inches

Second Leg Slot Length:

0.875 inches

Second Leg Slot Width:

0.437 inches

First Leg Thickness:

0.380 inches

Second Leg Thickness:

0.380 inches

First Leg Width:

10.130 inches

First Leg End Width:

9.370 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

3 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

Second leg width at angle is 10.130; left side tapers from point 0.750 from angle end to point 3.130 from angle; right side lower point is 2.07 from right edge with resulting width from these points down being 5.63 in.

Material:

Titanium alloy

Material Specification:

Mil-t-9046, comp ab-2, condition annealed military specification single material response

Surface Treatment:

Primer and paint

Surface Treatment Specification:

Mil-p-24441/29 military specification 1st treatment response and mil-p-24441/31 military specification 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-t-9046 spec.