

View Online at <https://aerobasegroup.com/nsn/5340-01-509-6427>

First Leg Length:

2.880 inches

Second Leg Length:

4.750 inches

Second Leg Width:

Between 3.630 inches and 5.630 inches

Second Leg End Width:

1.870 inches

Second Leg Distance Between Hole Centers Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.739 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.125 inches

Second Leg Slot Length:

0.875 inches

Second Leg Slot Width:

0.450 inches

First Leg Thickness:

0.380 inches

Second Leg Thickness:

0.380 inches

First Leg Width:

6.130 inches

First Leg End Width:

5.370 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

2nd leg is 6.130 at angle/top; left side tapers from point 0.75 from top on left edge to point 1.98 from top and 0.92 from left edge; right side tapers from point 0.75 from top on right edge to point 2.684 from top and 1.58 from right edge with resulting width from this point down 3.63 in.

Material:

Titanium alloy

Material Specification:

Mil-t-9046, comp ab-2, condition annealed military specification single material response

Surface Treatment:

Primer and paint

Surface Treatment Specification:

Mil-p-24441/29 military specification 1st treatment response and mil-p-24441/31 military specification 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-t-9046 spec.