

View Online at <https://aerobasegroup.com/nsn/5340-01-509-6427>

**First Leg Length:**

2.880 inches

**Second Leg Length:**

4.750 inches

**Second Leg Width:**

Between 3.630 inches and 5.630 inches

**Second Leg End Width:**

1.870 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.739 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.125 inches

**Second Leg Slot Length:**

0.875 inches

**Second Leg Slot Width:**

0.450 inches

**First Leg Thickness:**

0.380 inches

**Second Leg Thickness:**

0.380 inches

**First Leg Width:**

6.130 inches

**First Leg End Width:**

5.370 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

No hole

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**First Leg Chamfer Angle:**

45.0 degrees

**Second Leg Chamfer Angle:**

45.0 degrees

**Special Features:**

2nd leg is 6.130 at angle/top; left side tapers from point 0.75 from top on left edge to point 1.98 from top and 0.92 from left edge; right side tapers from point 0.75 from top on right edge to point 2.684 from top and 1.58 from right edge with resulting width from this point down 3.63 in.

**Material:**

Titanium alloy

**Material Specification:**

Mil-t-9046, comp ab-2, condition annealed military specification single material response

**Surface Treatment:**

Primer and paint

**Surface Treatment Specification:**

Mil-p-24441/29 military specification 1st treatment response and mil-p-24441/31 military specification 2nd treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-t-9046 spec.