

View Online at <https://aerobasegroup.com/nsn/5340-01-509-7625>

Mounting Hole Type:

Plain

First Leg Length:

2.050 inches

Second Leg Length:

2.050 inches

Furnished Items (non-core):

2 captive screws, low profile

Second Leg Width:

5.380 inches

First Leg Hole Diameter:

Between 0.154 inches and 0.157 inches

Second Leg Hole Diameter:

Between 0.154 inches and 0.159 inches

Second Leg Distance Between Hole Centers Along Width:

2.950 inches

Second Leg Distance Between Hole Centers Along Length:

1.090 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.425 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.155 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

2.950 inches

Center Section Width:

5.380 inches

Center Section Thickness:

0.125 inches

First Leg Width:

5.380 inches

First Leg Corner Radius:

0.060 inches

First Leg Distance Between Hole Centers Along Width:

2.950 inches

First Leg Distance Between Hole Centers Along Length:

1.090 inches

First Leg Distance From Edge To Hole Center Along Width:

1.375 inches

First Leg Distance From Edge To Hole Center Along Length:

0.155 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Product Name:

Bracket, mounting, 1553 bus coupler

Material:

Aluminum alloy 5052

Material Specification:

Astm b209, temper h32 assn standard single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.